





# Lechner

SOLUTIONS FOR PROFESSIONAL CONSTRUCTION



## FIELDS OF APPLICATION

-  RESILIENT LINE
-  WOOD LINE
-  MARINE LINE
-  ARTIFICIAL GRASS LINE
-  EQUIPMENT AND ACCESSORIES LINE

# DILUENTE CH 400

UNIVERSAL POLYURETHANE THINNER FOR SOLVENT-BASED COATED PRODUCTS

## DESCRIPTION AND USES

PRODUCT FOR PROFESSIONAL USE ONLY

Universal polyurethane thinner, with exceptional solvent power, slow and wide evaporation. To be used with Lechner solvent-based polyurethane coatings at a rate of around 5%.

### PRODUCT FEATURES



**Additives - Latex**



**Suitable for indoor use**



**Storage**  
24 months in the original sealed packages



**Appearance**  
Liquid



**Color**  
Transparent



**Chemical base**  
Mixture of organic solvents



**Operating temperature**  
+10 - +30 °C

### METHOD OF USE

Add around 5% to Lechner solvent-based coatings and shake vigorously before application.

### INSTRUCTIONS

**FOR SAFETY AND DISPOSAL:** Consult the relevant safety data sheet before using the product. Protect your hands and eyes during use. Product and its vapors are flammable; keep away from flames, sparks and do not smoke. Ventilate the room during and after use. Follow applicable safety regulations. Do not dispose of any residue into the ground, waterways or drains. For the disposal of the product and other waste deriving from the activity, scrupulously follow the provisions of Legislative Decree 152/2006 and subsequent modifications and integrations (Environmental Consolidation Act). For further information please contact our Technical Assistance Department. The content of this sheet integrates and replaces and cancels the previous one.

**WARNINGS:** The data provided in this data sheet reflect our best theoretical and practical knowledge. However, since it is not possible for us to go into every detail, such information should not be considered as binding. In cases of doubt, please contact our technical offices.