



SOLUTIONS FOR PROFESSIONAL CONSTRUCTION



#### FIELDS OF APPLICATION



RESILIENT LINE



WOOD LINE



MARINE LINE



ARTIFICIAL GRASS LINE



EQUIPMENT AND ACCESSORIES LINE

# DILUENTE PU

THINNER FOR POLYURETHANE PRIMERS

## DESCRIPTION AND USES

PRODUCT FOR PROFESSIONAL USE ONLY

Mixture of high quality solvents for diluting the PRIMERS of the PU series (PRIMER PU, PRIMER PU 150 SPEED, PRIMER PU 300).

### PRODUCT FEATURES



**Additives - Latex**



**Suitable for indoor use**



**Storage**  
24 months in the original  
sealed packages



**Appearance**  
Liquid



**Color**  
Transparent



**Chemical base**  
Mixture of organic solvents



**Operating temperature**  
+10 - +30 °C

### METHOD OF USE

For diluting the PRIMERS of the PU series, see the relative technical data sheets.

### INSTRUCTIONS

**FOR SAFETY AND DISPOSAL:** Consult the relevant safety data sheet before using the product. Protect your hands and eyes during use. Product and its vapors are flammable; keep away from flames, sparks and do not smoke. Ventilate the room during and after use. Follow applicable safety regulations. Do not dispose of any residue into the ground, waterways or drains. For the disposal of the product and other waste deriving from the activity, scrupulously follow the provisions of Legislative Decree 152/2006 and subsequent modifications and integrations (Environmental Consolidation Act). For further information please contact our Technical Assistance Department. The content of this sheet integrates and replaces and cancels the previous one.

**WARNINGS:** The data provided in this data sheet reflect our best theoretical and practical knowledge. However, since it is not possible for us to go into every detail, such information should not be considered as binding. In cases of doubt, please contact our technical offices.