






# Lechner

SOLUTIONS FOR PROFESSIONAL CONSTRUCTION



## FIELDS OF APPLICATION

-  RESILIENT LINE
-  MARINE LINE
-  WOOD LINE
-  ARTIFICIAL GRASS LINE
-  EQUIPMENT AND ACCESSORIES LINE

# FASTER

ACCELERATING ADDITIVE FOR POLYURETHANE ADHESIVES

## DESCRIPTION AND USES

PRODUCT FOR PROFESSIONAL USE ONLY

Accelerating additive for two-component polyurethane adhesives such as GOMMAPUR, GREEN PUR, GREEN PUR PLUS, LEGNOPOL 2000, where fast setting times and accelerated floor commissioning are required.

### PRODUCT FEATURES



**Suitable for indoor use**



**Suitable for outdoor use**



**Storage**

24 months in the original sealed packages



**Appearance**

Liquid



**Color**

Straw yellow



**Chemical base**

Blend of selected additives



**Operating temperature**

+10 - +30 °C

### METHOD OF USE

To speed up setting and laying times, FASTER can be added to the 10 kg mixture of polyurethane adhesives such as GOMMAPUR, GREEN PUR, GREEN PUR PLUS, LEGNOPOL 2000. If the entire 100 ml vial of FASTER is used, the pot life of the product drops to about half in standard environmental conditions, resulting in a final setting time of less than 48 hours. Of course, it is possible to use less or more than 100 ml of FASTER to decrease the pot life in the desired amount (please contact our technical offices for any clarifications).

### INSTRUCTIONS

**FOR SAFETY AND DISPOSAL:** Consult the relevant safety data sheet before using the product. Protect your hands and eyes during use. Follow applicable safety regulations. Do not dispose of any residue into the ground, waterways or drains. For the disposal of the product and other waste deriving from the activity, scrupulously follow the provisions of Legislative Decree 152/2006 and subsequent modifications and integrations (Environmental Consolidation Act). For further information please contact our Technical Assistance Department. The content of this sheet integrates and replaces and cancels the previous one.

**WARNINGS:** The data provided in this data sheet

reflect our best theoretical and practical knowledge. However, since it is not possible for us to go into every detail, such information should not be considered as binding. In cases of doubt, please contact our technical offices.