

DESCRIPTION AND USES

PRODUCT FOR PROFESSIONAL USE ONLY

KIPOS OIL is a high-solids, deeply penetrating exterior wood finish based on modified natural oils. Its intrinsically low viscosity allows for optimal penetration into the wood substrate, ensuring effective impregnation even with a high solids content and providing long-lasting protective performance. The product contains natural substances and specific additives acting as UV filters, offering protection against ultraviolet radiation and harmful weathering agents. KIPOS OIL enhances and preserves the natural appearance of the wood while providing water-repellent and protective properties.

Also available in pigmented versions.

PRODUCT FEATURES



Application
Brush



Suitable for outdoor use



Time between coats
6-8 hours
Final hardening time
24 hours



Chemical base
Blend of natural oils and resins with UV absorbers



Storage
24 months when stored in original, unopened containers in a cool, dry place, protected from direct sunlight and frost (storage temperature >10 °C).



Appearance
Liquid



Color
Neutral



Yield
16-20 ml/sqm per coat



Operating temperature
+10 - +30 °C



Mix before use



Cleaning
SOLVENTE CH500 (while the product is fresh)

USAGE

Preparation of the substrate

Dirty / weathered decking: remove dust, thoroughly wet the surface, then apply WOOD RENEWER brightening cleaner for exterior wood using a brush (see technical data sheet).

Very dirty, heavily weathered decking, with mould and dark stains: remove dust, thoroughly wet the surface, then apply WOOD RENEWER STRONG, an intensive brightening/stripping cleaner for exterior wood, using a brush (see technical data sheet).

Neutralize the darkened wood surface with WOOD RENEWER.

New or lightly soiled decking: thoroughly wash the surface with the pH-neutral detergent DECK SOAP.

Application of KIPOS OIL: lightly sand the surface to remove any roughness; otherwise, proceed directly with product application.

The product is ready to use. Shake the container vigorously before opening and stir well before use. Apply one well-spread coat using a roller, taking care to avoid excess product.

When the floor is walkable, after approximately 6-8 hours, apply a second coat without sanding. Allow the surface to dry completely for approximately 24 hours.

KIPOS OIL is available in the following colours: neutral, teak, wengé, iroko, mahogany, dark walnut, grey, black ebony.

The pigmented versions provide greater protection to the wood compared to the neutral version.

Cleaning and maintenance: for routine cleaning of decking treated with KIPOS OIL, use DECK SOAP.

For extraordinary and/or seasonal maintenance (generally 1-2 times per year, or whenever deemed necessary), use WOOD RENEWER and/or WOOD RENEWER STRONG (see the relevant technical data sheets), depending on the condition of the wooden decking.

OTHER INFORMATION

The drying times indicated in the characteristics refer to an ambient temperature of +20°C and a relative air humidity of 50%. However, depending on the type of wood being treated, both the drying times and the weight required may vary (very absorbent woods require higher weights and dry faster). Drying times are also strongly influenced by weather conditions. Due to its oxidative nature, the oil reacts much faster on sunny days with increased air circulation, significantly reducing working and drying times.

Before applying KIPOS OIL, make sure that weather conditions are suitable, as rain may cause the oil to be washed off.

INSTRUCTIONS

FOR SAFETY AND DISPOSAL: Consult the relevant safety data sheet before using the product. During use, it is recommended to protect your hands with gloves and to observe all applicable safety regulations. Wood shavings, cotton cloths, paper and similar products soaked in liquid product and left in such conditions may cause spontaneous combustion. Therefore ensure good ventilation to allow the product to dry quickly or wet them with water before disposal. Do not dispose of any residue into the ground, waterways or drains. For the disposal of the product and other waste deriving from the activity, scrupulously follow the provisions of the DLgs. 152/2006 and s.m.i. (Environmental Consolidation Act). For further information please contact our Technical Assistance Department. The content of this current sheet supplements and replaces the previous version, rendering it null and void.

WARNINGS: The data provided in this data sheet reflect our best theoretical and practical knowledge. However, since it is not possible for us to go into every detail, such information should not be considered as binding. In cases of doubt, please contact our technical offices.

Product conforms to 2004/42/EC regulations:

Wood impregnators that form a film of minimal thickness, cat A(f). Limit value 700 g/l. VOC content of the ready-for-use product 382.5 g/l