

Lechner

SOLUTIONS FOR PROFESSIONAL CONSTRUCTION



FIELDS OF APPLICATION

-  RESILIENT LINE
-  MARINE LINE
-  EQUIPMENT AND ACCESSORIES LINE
-  ~~WOOD LINE~~
-  ARTIFICIAL GRASS LINE

OIKOS OIL WAX

WAX OIL FOR WOOD FLOORS

DESCRIPTION AND USES

PRODUCT FOR PROFESSIONAL USE ONLY

OIKOS OIL WAX is a finish based on micronized natural oils and waxes specifically for indoor wood floors. Reinforced with high quality resins, it enhances the beauty of the wood and provides excellent resistance to water and all types of stains. The addition of waxes gives the surface a natural effect, a high softness to the touch together as well as increased opacity.

PRODUCT FEATURES



Application
Brush



Application
Clean cloth



Suitable for indoor use



Recoating time
6-8 hours
Walkability time
12 hours



Chemical base
Blend of natural oils and waxes



Storage
24 months in the original packaging in a cool and dry place, protected from sun and cold (>10°C). Once the container is open, close it carefully after each use.



Appearance
Liquid



Color
Transparent



Yield
40-100 mL/sqm per coat



Operating temperature
+18 - +30 °C



Mix before use



Cleaning
CH500 Solvent (while the product is fresh)

USAGE

Application: the product is ready to use; shake the contents vigorously before opening it and mix well before use, it can be applied by cloth or brush.

Apply a first coat evenly on a previously sanded surface, which must be clean and free of oil and grease. Allow to dry for 6-8 hours then sand with 220/240 grit paper. Proceed with the application of the second coat.

It is advisable to ventilate the rooms to facilitate the drying process.

Cleaning and maintenance: for routine cleaning of wood floors treated with OIKOS OIL WAX use OK CLEAN. In case of stubborn dirt, use the strong detergent OIKOS STRONG.

OTHER INFORMATION

The drying times indicated in the characteristics refer to an ambient temperature of +20°C and a relative air humidity of 50%. However, depending on the type of wood treated, both the drying times and the necessary weight may vary. Some exotic or heavily stained woods may inhibit or considerably lengthen the curing process of OIKOS OIL WAX. In this case, apply a light first coat and ventilate the rooms suitably.

INSTRUCTIONS

FOR SAFETY AND DISPOSAL: Consult the relevant safety data sheet before using the product. During use, it is recommended to ventilate the room and protect your hands with gloves. Observe all applicable safety regulations during use. Wood shavings, cotton cloths, paper and similar products soaked in liquid product and left in such conditions may cause spontaneous combustion. Therefore ensure good ventilation to allow the product to dry quickly or wet them with water before disposal. Do not dispose of any residue into the ground, waterways or drains. For the disposal of the product and other waste deriving from the activity, scrupulously follow the provisions of the DLgs.

152/2006 and s.m.i. (Environmental Consolidation Act). For further information please contact our Technical Assistance Department. The content of this current sheet supplements and replaces the previous version, rendering it null and void.

WARNINGS: The data provided in this data sheet reflect our best theoretical and practical knowledge. However, since it is not possible for us to go into every detail, such information should not be considered as binding. In cases of doubt, please contact our technical offices.