

# Lechner

SOLUTIONS FOR PROFESSIONAL CONSTRUCTION



## FIELDS OF APPLICATION

-  RESILIENT LINE
-  WOOD LINE
-  MARINE LINE
-  ARTIFICIAL GRASS LINE
-  EQUIPMENT AND ACCESSORIES LINE

# PU BLOCK

IGRONDURENT POLYURETHANE RESIN FOR SEALING OLD WOODEN FLOORS

## DESCRIPTION AND USES

PRODUCT FOR PROFESSIONAL USE ONLY

Single-component, hygro-hardening, water- and solvent-free, self-curing, high-solids polyurethane resin. Suitable in the renovation of pre-existing wooden flooring for the blocking of creaking or not perfectly adherent elements.

### PRODUCT FEATURES

**Application**

Flexible stainless steel spatula

**Suitable for indoor use****Drying time**

48 hours

**Sanding time**

24 hours

**Storage**

12 months in the original sealed containers

**Appearance**

Liquid

**Color**

Brown

**Chemical base**

Polyurethane resin

**Yield**

according to use

**Operating temperature**

+10 - +30 °C

**Cleaning**

CH500 Solvent (while the product is fresh)

### METHOD OF USE

Sand down the existing flooring, taking care to remove the pre-existing finish in order to facilitate the penetration of the resin.

Apply PU BLOCK with a spatula, helping the resin to get inside the joints as much as possible, or in any case between the elements of the flooring.

It is advisable to beat the treated surface in order to guarantee the best spreading of the resin in the cavities underneath the parquet. Wait for complete drying and proceed with sanding.

### OTHER INFORMATION

Odorless and solvent-free product so it can be used in inhabited areas. The indicated drying times may vary depending on the depth of the gaps and the relative humidity of the air.

### INSTRUCTIONS

**FOR SAFETY AND DISPOSAL:** Consult the relevant safety data sheet before using the product. Gloves are recommended during use. Ventilate the room during and after use. Follow applicable safety regulations. Do not dispose of any residue into the ground, waterways or drains. For the disposal of the product and other waste deriving from the activity, scrupulously follow the provisions of the DLgs. 152/2006 and s.m.i. (Environmental Consolidation Act). For further information please contact our Technical Assistance Department. The content of this sheet integrates and replaces and cancels the previous one.

**WARNINGS:** The data provided in this data sheet reflect our best theoretical and practical knowledge. However, since it is not possible for us to go into every detail, such information should not be considered as binding. In cases of doubt, please contact our technical offices.