

Lechner

SOLUTIONS FOR PROFESSIONAL CONSTRUCTION



FIELDS OF APPLICATION

-  RESILIENT LINE
-  WOOD LINE
-  MARINE LINE
-  ARTIFICIAL GRASS LINE
-  EQUIPMENT AND ACCESSORIES LINE

SEAL WOOD

COLORED SEALANT FOR WOODEN FLOORING

DESCRIPTION AND USES

PRODUCT FOR PROFESSIONAL USE ONLY

Solvent-free acrylic sealant in water dispersion suitable for gluing and sealing cracks in the laying of parquet or baseboards. Also suitable for gluing corner pieces.

PRODUCT FEATURES



Application
Silicone gun



Suitable for indoor use



Laying time

45-60 minutes

Final curing time

1 mm: 1 day; 5 mm: 7 days; 10 mm: 14 days



Storage

24 months in the original sealed containers



Appearance

Thixotropic paste



Color

Various colors (White, Doussiè, Medium Walnut, Oak, Dark Walnut)



Chemical base

Acrylic resin



Operating temperature

+5 - +40 °C



Cleaning

Water (while the product is fresh)

CERTIFICATIONS



Solvent-free product

METHOD OF USE

Substrates must be dry, absorbent, flat, and resistant to compression and traction. They must also be free of dust, removable parts, paint, waxes, oils, rust or traces of plaster. Insert the cartridge in the appropriate gun, cut the nozzle and apply the SEAL WOOD taking care not to incorporate air during application. At the end of the application smooth the joint with spatula or other suitable tool, in case of shrinkage repeat the application. After about 24 hours SEAL WOOD can be sanded and recoated.

OTHER INFORMATION

Single-component, paintable, easy-to-apply sealant that cross-links quickly at room temperature. It is compatible with most building materials such as wood, cement, stone, marble, ceramic etc. It does not create tension in the expansion joint because it is elastic and flexible. SEAL WOOD cannot be applied on wet surfaces. In the following table you can calculate the recommended consumption of SEAL WOOD based on the width and depth of the joints.

FOR SAFETY AND DISPOSAL: Consult the relevant safety data sheet before using the product. Gloves are recommended during use. Ventilate the room during and after use. Follow applicable safety regulations. Do not dispose of any residue into the ground, waterways or drains. For the disposal of the product and other waste deriving from the activity, scrupulously follow the provisions of the DLgs. 152/2006 and s.m.i. (Environmental Consolidation Act). For further information please contact our Technical Assistance Department. The content of this sheet integrates and replaces and cancels the previous one.

WARNINGS: The data provided in this data sheet reflect our best theoretical and practical knowledge. However, since it is not possible for us to go into every detail, such information should not be considered as binding. In cases of doubt, please contact our technical offices.

INSTRUCTIONS

DEPTHS ↓	WIDTH ↔					
	3 mm	7 mm	10 mm	12 mm	19 mm:	25 mm
3 mm	33 m	14 m	10 m	8 m	5 m	4 m
5 mm	20 m	8 m	6 m	5 m	3 m	2 m
7 mm	14 m	6 m	4 m	4 m	2 m	2 m
10 mm	10 m	4 m	3 m	2 m	2 m	1 m