

# Lechner

SOLUTIONS FOR PROFESSIONAL CONSTRUCTION



## FIELDS OF APPLICATION

-  RESILIENT LINE
-  MARINE LINE
-  WOOD LINE
-  ARTIFICIAL GRASS LINE
-  EQUIPMENT AND ACCESSORIES LINE

# TAK 02

MULTIFUNCTIONAL ADHESIVE FOR GLUING WOODEN SKIRTING BOARDS

## DESCRIPTION AND USES

PRODUCT FOR PROFESSIONAL USE ONLY

Solvent-free acrylic adhesive in water dispersion specifically designed for gluing wooden skirting boards. TAK 02 is also suitable for bonding polyurethane, polystyrene, ceramic, plaster, marble, plastic and fiber cement.

### PRODUCT FEATURES



**Application**  
Caulking gun for silicone



**Suitable for internal use**



**Open time**  
45-60 hours  
**Final setting time**  
24 hours



**Chemical base**  
Acrylic resin



**Storage**  
24 months in original sealed package



**Appearance**  
Paste



**Color**  
White



**Operating temperature**  
+5 - +40°C



**Cleaning**  
Water (as long as the product is fresh)

### CERTIFICATIONS



**Solvent-free product**

### MODE OF USE

Surfaces to be bonded must be clean, free of dust, grease and loose foreign matter. Next, cut the cartridge nozzle to the desired diameter and apply the product. TAK 02 should be applied in sufficient quantity to ensure multiple points of grip between surfaces to be assembled. TAK 02 can be painted over with Lechner coatings after 1.5 - 2 hours. At least one of the two substrates must be an absorbent type. In case of low absorbent surfaces wait 5 - 10 minutes before bonding the materials. Do not use below +5°C temperature.

**WARNINGS:** The data provided in this data sheet reflect our best theoretical and practical knowledge. However, since it is not possible for us to go into every detail, such information should not be considered as binding. In cases of doubt, please contact our technical offices.

### OTHER INFORMATION

The application and bonding times indicated in the characteristics refer to an ambient temperature of +20°C and a relative air humidity of 50%. Set the glue and wood to the conditions of the installation rooms.

### INSTRUCTIONS

**FOR SAFETY AND DISPOSAL:** Consult the relevant safety data sheet before using the product. During use it is advisable to ventilate the room, protect your hands with gloves and follow the safety rules in force. Do not dispose of any residue into the ground, water supplies or drains. For the disposal of the product and other waste deriving from the work carried out, scrupulously comply with the provisions of Legislative Decree no. 152/2006 and subsequent amendments and integrations. (Environmental Consolidation Act). For further information please contact our Technical Assistance Department. The content of this sheet integrates and replaces the previous version, rendering it null and void.