

DESCRIPTION AND USES

PRODUCT FOR PROFESSIONAL USE ONLY

OIKOS OIL 2K is a high-solids, two-component oil based on vegetable oils and resins, designed for parquet floors with excellent performance. It provides high abrasion resistance, effective protection for parquet, and a natural feel to the touch. Suitable for interior use.

OIKOS OIL 2K is recommended for all types of wood, giving a natural touch effect.

PRODUCT FEATURES



Application
Single-brush cleaner



Suitable for indoor use



Dust free time

6-8 hours

Sanding time

6-8 hours

Final hardening time

24-48 hours



Catalysis ratio

100:10 (A:B) for domestic use

100:30 (A:B) for high-traffic surfaces



Chemical base

Vegetable oils and resins



Storage

24 months in the original packaging in a cool and dry place, protected from sun and cold (>10°C).

Once the container is open, close it carefully after each use.



Appearance

Liquid



Color

Neutral



Yield

80-90 g/sqm per coat



Operating temperature

+10 - +30 °C



Mix before use



Cleaning

SOLVENTE CH500 (while the product is fresh)

USAGE

Surface preparation: remove any maintenance waxes, grease, or residues from the parquet floor. Sand the parquet and carry out filling as required. Sand with 100–120 grit abrasive paper, then completely vacuum all dust.

Application: mix part A only and pour it into a clean container. Do not shake part B; pour it into part A and mix thoroughly. Apply the product evenly using a single-disc machine, avoiding excess buildup. Allow the product to dry for at least 8 hours. Lightly sand with 180–220 grit sandpaper or abrasive mesh, vacuum, and apply a second coat.

OIKOS OIL 2K is compatible with the OIKOS PRIME impregnating primer, to obtain a complete oil finishing system.

disposal. Do not dispose of any residue into the ground, waterways or drains. For the disposal of the product and other waste deriving from the activity, scrupulously follow the provisions of the DLgs. 152/2006 and s.m.i. (Environmental Consolidation Act). For further information please contact our Technical Assistance Department. The content of this current sheet supplements and replaces the previous version, rendering it null and void.

WARNINGS: The data provided in this data sheet reflect our best theoretical and practical knowledge. However, since it is not possible for us to go into every detail, such information should not be considered as binding. In cases of doubt, please contact our technical offices.

OTHER INFORMATION

The drying times indicated in the technical characteristics refer to an ambient temperature of +20°C and a relative air humidity of 50%. However, depending on the type of wood (e.g. exotic or low-porosity woods), the application method, and the applied quantity, drying times and consumption may vary from those indicated.

INSTRUCTIONS

FOR SAFETY AND DISPOSAL: Consult the relevant safety data sheet before using the product. During use, it is recommended to ventilate the room and protect your hands with gloves. Observe all applicable safety regulations during use. Wood shavings, cotton cloths, paper and similar products soaked in liquid product and left in such conditions may cause spontaneous combustion. Therefore ensure good ventilation to allow the product to dry quickly or wet them with water before

Product conforms to 2004/42/EC regulations:

Wood impregnators that form a film of minimal thickness, cat A(f). Limit value 700 g/l. VOC content of the ready-for-use product 493 g/l