

DESCRIPTION AND USES

PRODUCT FOR PROFESSIONAL USE ONLY

OIKOS OIL CEROSO FORTE is a single-component impregnating oil based on vegetable oils and waxes enriched with resins, designed for parquet floors and wooden elements (doors, windows, skirting boards). Its formulation provides excellent abrasion resistance, a soft touch, and a matte finish. Suitable for interior use.

OIKOS OIL CEROSO FORTE is ready to use and suitable for all types of wood, especially absorbent or porous woods. A two-coat application is recommended for optimal finishing.

PRODUCT FEATURES



Application
Brush



Application
Short-haired roller



Application
Single-brush cleaner



Suitable for indoor use



Dust free time
1-2 hours

Sanding time
6-8 hours

Final hardening time
9-12 hours



Chemical base
Vegetable oils and waxes modified with resins



Storage
24 months in the original packaging in a cool and dry place, protected from sun and cold (>10°C). Once the container is open, close it carefully after each use.



Appearance
Liquid



Color
Neutral



Yield
80-90 g/sqm for coat



Operating temperature
+10 - +30 °C



Mix before use



Cleaning
SOLVENTE CH500 (while the product is fresh)

USAGE

Surface preparation: remove any maintenance waxes and grease from the parquet floor. Sand the surface and proceed with filling as required. Perform final sanding with 150-180 grit sandpaper, then thoroughly vacuum to remove all dust.

Application: the product is ready to use; stir well before use. It can be applied using a roller, cloth, brush, or single-disc machine.

Apply the product evenly, avoiding excess build-up. Allow to dry for at least 6-8 hours. Lightly sand with 220-240 grit sandpaper, vacuum thoroughly, and apply a second coat.

OTHER INFORMATION

The drying times indicated in the technical characteristics refer to an ambient temperature of +20°C and a relative air humidity of 50%. However, depending on the type of wood (e.g. exotic or low-porosity woods), the application method, and the applied quantity, drying times and consumption may vary from those indicated.

INSTRUCTIONS

FOR SAFETY AND DISPOSAL: Consult the relevant safety data sheet before using the product. During use, it is recommended to ventilate the room and protect your hands with gloves. Observe all applicable safety regulations during use. Wood shavings, cotton cloths, paper and similar products soaked in liquid product and left in such conditions may cause spontaneous combustion. Therefore ensure good ventilation to allow the product to dry quickly or wet them with water before disposal.

Do not dispose of any residue into the ground, waterways or drains. For the disposal of the product and other waste deriving from the activity, scrupulously follow the provisions of the DLgs. 152/2006 and s.m.i. (Environmental Consolidation Act). For further information please contact our Technical Assistance Department. The content of this current sheet supplements and replaces the previous version, rendering it null and void.

WARNINGS: The data provided in this data sheet reflect our best theoretical and practical knowledge. However, since it is not possible for us to go into every detail, such information should not be considered as binding. In cases of doubt, please contact our technical offices.

Product conforms to 2004/42/EC regulations:

Wood impregnators that form a film of minimal thickness, cat A(f). Limit value 700 g/l. VOC content of the ready-for-use product 493 g/l