FLOOR CLEAN DAILY

DAILY CLEANER FOR RESILIENT FLOORS, LAMINATE, LVT AND SPC FLOORING

MAINTENANCE FOR RESILIENT FLOORS

DESCRIPTION AND USES

PRODUCT FOR PROFESSIONAL USE ONLY

Neutral pH detergent for the daily cleaning of all resilient floors, laminate, LVT and SPC flooring, with no rinsing required. Suitable for removing light dirt, it leaves surfaces clean, shiny and pleasantly fragranced.

PRODUCT FEATURES

Application
Clean cloth

Application
Mop

Suitable for indoor use

Dilution
Water

Storage
Storage
36 months in original

Appearance
Liquid

Colour
Trasparent

Base chimica
Reg. (CE) N° 648/2004:< 5% non-ionic surfactants, Citronellol, Geranial; preservatives: 5-cloro-2-metil-2H-isotiazol-3-one e 2 metil 2H-isotiazol-3-one.
Contains: 5-chloro-2-methyl-4-isothiazolin-3-one e 2-methyl-2H-isothiazol-3-one

Protect from frost

METHOD OF USE

Remove dust from the surface using a vacuum cleaner. Prepare a 3–5% solution in water (30–50 g of FLOOR CLEAN DAILY per litre of water), soak a clean cloth or mop in the solution and clean the surface. At this dilution, FLOOR CLEAN DAILY does not affect metallized wax coatings.

For quick cleaning of all washable surfaces, the product can be diluted to 10–20% with water and sprayed directly onto the surface. Suitable for use with scrubber-dryer machines. No rinsing required.

For the removal of heavy dirt, the use of the alkaline pH detergent FLOOR CLEAN PRO is recommended. Its degreasing and wax-removing action makes it suitable for extraordinary maintenance.

INSTRUCTIONS

FOR SAFETY AND DISPOSAL: Consult the relevant safety data sheet before using the product. Gloves are recommended during use. Ventilate the room during and after use. Follow all applicable safety regulations. Do not dispose of any surplus in the ground, waterways or drains. For disposal of the product and other waste derived from its use, adhere closely to the provisions of Legislative Decree no. 152/2006 and subsequent amendments and additions of the Consolidated Environmental Act (Testo Unico Ambientale). For further information, please contact our Technical Assistance Department. The content of this current sheet supplements and replaces the previous version, rendering it null and void.

WARNINGS: The data provided in this technical data sheet reflect our best theoretical and practical knowledge. However, it is not possible for us to consider every detail, therefore this information should not be considered as binding. In the event of any doubt, contact our technical offices.

Lechner S.p.A. • 15061 Arquata Scrivia (AL) Italy • p. +390143636103 • info@lechnerspa.it