

ODORLESS CONTACT ADHESIVE WITH INSTANT BONDING

DESCRIPTION AND USES PRODUCT FOR PROFESSIONAL USE ONLY

Double-spreading adhesive based on an aqueous synthetic resin dispersion, particularly suitable for gluing plastic laminates, and PVC and rubber profiles, flooring and coatings on absorbent or poorly absorbent surfaces, using a trowel. As well as ensuring high performance, its unique solvent-free and completely odorless formulation makes it completely safe to use even in the most "delicate" situations, where it is not possible to use solvent-based products, such as schools, hospitals, residential buildings.

PRODUCT FEATURES



Application
Brush



Application
Lechner toothed trowel no.1



Suitable for indoor use



Suitable for under-floor heating systems



Suitable for wheelchairs



Waiting Time 30-120 minutes
Open time 5 hours
Immediate dry-to-walk-on time
Final curing time 48 hours



Storage
12 months in original sealed packaging



Appearance
Paste



Color
Gray



Chemical base
Synthetic resins in aqueous dispersion



Consumption
150g/m² per coating



Operating temperature
+10 - +30 °C



Susceptible to frost



Double coating



Cleaning
Water (as long as the product is fresh)



Solvent-free product

CERTIFICATIONS

METHOD OF USE

The substrate must be compact, in good condition, clean, established, permanently dry and free from detaching substances such as oils, waxes, excess dust, etc. An even coat of adhesive must be applied on both surfaces using a fine notched trowel. When gluing the sheet materials, particularly thin ones such as plastic laminates, spreading the adhesive evenly is a key factor in obtaining perfectly flat and regular gluing. Adhesive build-up may be more visible due to the high solid residue. It is recommended to wait about 30 to 120 minutes, depending on temperature, ambient humidity and porosity of the surfaces. After this time, a slight skin may form on the surface of the adhesive, however this does not impact the effectiveness of the adhesive films during pressing, provided that this is done within 120 minutes after coating. Maintaining proper drying times and uniformity of pressing are essential to ensure quality gluing. Bonding is instant and is at its best a few days after gluing (about 48 hours).

OTHER INFORMATION

The application and gluing times indicated in the product features correspond to an ambient temperature of +20°C and a relative air humidity of 50%. The product and the flooring should be stored in the conditions of the desired rooms. The fixed floors can only be welded after 24 hours. Avoid exposure to excessively high and low temperatures.

INSTRUCTIONS

FOR SAFETY AND DISPOSAL: Consult the relevant safety data sheet before using the product. Gloves are recommended during use. Ventilate the room during and after use. Follow all applicable safety regulations. Do not dispose of any residue in the ground, waterways or drains. To dispose of the product and other waste deriving from the activity, adhere closely to the provisions of Legislative Decree no. 152/2006 and subsequent amendments and additions of the Consolidated Environmental Act (Testo Unico Ambientale). For further information, please contact our Technical Assistance Department. The content of this sheet integrates and replaces the previous version, rendering it null and void.

WARNINGS: The data provided in this data sheet reflects our best theoretical and practical knowledge. However, it is not possible for us to consider every detail, therefore this information should not be considered as binding. In the event of any doubt, please contact our technical offices.