MASTIPREN LP53

UNIVERSAL HIGHLY STRONG DOUBLE COATING FLUID ADHESIVE

DESCRIPTION AND USES

PRODUCT FOR PROFESSIONAL USE ONLY

Polychloroprene-based double coating solvent adhesive, suitable for gluing baseboards, plastic laminates, various profiles, steps, PVC flooring and wall coverings, carpets, linoleum, rubber, cork, in sheets or tiles, on absorbent or non-absorbent surfaces. MASTIPREN LP 53 is toluol-free.

PRODUCT FEATURES



Application
Lechner toothed trowel no. 1



Double coating



Suitable for indoor use



Suitable for under-floor heating systems



Suitable for wheelchairs



Waiting time
15-20 minutes
Open time
40 minutes
Dry-to-walk-on time
immediate
Final setting time
48 hours



Appearance
Paste



Color
Yellow



Chemical base
Polychloroprene in solvent



Storage
12 months in original sealed packaging



Consumption
150 g/m^2 per coating



Operating temperature
+10 - +30 °C



Cleaning
Solvent CH 500 (as long as the product is fresh)



Mix before use

METHOD OF USE

The substrate must be compact, in good condition, established, permanently dry and free from detaching substances such as oils, waxes, excess dust, etc. Maximum allowable moisture content:
- Cementitious substrates: max. 2.0%; with underfloor heating 1.7%.
- Gypsum or anhydrite substrates: max. 0.5%; with underfloor heating 0.2%.

It is recommended to check that there is no rising moisture, in which case it is not possible to install. Substrates with an insufficiently flat or uneven laying surface can be leveled with cement-based leveling compounds, such as LIVELLANTE 140M, ULTRADUR, RASODUR, LEVELFAST, LEVELFAST S or RASODUR MAXI. Mix the product before use. Use a small-toothed trowel to apply the adhesive on the substrate and on the back of the material to be laid, taking care to incorporate any residual surface dust. Wait 15-20 minutes to allow the solvents to evaporate, then, once both surfaces are completely dry, press the surface to ensure full contact with the adhesive layer while gluing. Once the materials have been glued, the installation cannot be altered. A few hours before gluing, remove the wall covering from its packaging, laying it on the floor to reduce its tension and allow it to acclimatize to the working environment. Avoid exposure to excessively high temperatures.

OTHER INFORMATION

The application and gluing times indicated in the product features correspond to an ambient temperature of +20°C and a relative air humidity of 50%. The product and the flooring should be stored in the conditions of the desired rooms. It is always recommended to check the materials to be laid for compatibility and accelerated aging, especially if they are particularly thin, light-colored or new, so dyes or plasticizers contained within the coverings are not transferred to other areas. The fixed floors can only be welded after 24 hours. Avoid exposure to excessively high temperatures.

INSTRUCTIONS

FOR SAFETY AND DISPOSAL: Consult the relevant safety data sheet before using the product. Gloves are recommended during use. Ventilate the room during and after use. Follow all applicable safety regulations. Do not dispose of any residue in the ground, waterways or drains. To dispose of the product and other waste deriving from the activity, adhere closely to the provisions of Legislative Decree no. 152/2006 and subsequent amendments and additions of the Consolidated Environmental Act (Testo Unico Ambientale). For further information, please contact our Technical Assistance Department. The content of this sheet integrates and replaces the previous version, rendering it null and void.

WARNINGS: The data provided in this data sheet reflects our best theoretical and practical knowledge. However, it is not possible for us to consider every detail, therefore this information should not be considered as binding. In the event of any doubt, please contact our technical offices.

Lechner S.p.A. • 15061 Arquata Scrivia (AL) Italy • p. +390143636103 • info@lechnerspa.it